



RECOMMENDED P.C.B. LAYOUT(1.0~1.60±0.05)

NOTES:

1. ELECTRONIC:

CONTACT RESISTANCE: 30mohm MAX  
 INSULATION RESISTANCE: 1000 Mohm MIN  
 WITHSTAND VOLTAGE: AC 500V, 1min.

2. MECHANICAL:

STANDARD DURABILITY: 1500 CYCLES.

HIGH DURABILITY: 5000 CYCLES

3. ENVIRONMENT CHARACTERISTICS:

OPERATING TEMPERATURE: -25°C TO +85°C

4. PART NO.

SUS F 009 9 XX 2 023

USB SERIES

FEMALE

9PIN

PITCH SERIES

RUNNING NO.  
 2=DIP TYPE  
 00=GOLD FLASH  
 05=5U" AU  
 15=15U" AU

5. 标有“▲”为重点管控尺寸。

6. MATERIAL LIST:

3	SHELL	1	COPPER ALLOY	NI PLATED
2	CONTACT	9	COPPER ALLOY	AU/TIN PLATED
1	HOUSING	1	LCP	(UL 94V-0) BLACK
No.	PART NAME	QTY	MATERIAL	REMARK

Shenzhen City Xiangyunfeiwu  
 Technology Co., Ltd.

未注公差:	X, XX, XXX, XXXX	±0.38, ±0.25, ±0.15	设计: 冯应明		日期: 2010.08.12	品名: USB 3.0 A 母沉板插, 50 DTP (无卷边)
角度:	XX, XXX, XXXX	±2°, ±1°	第三视图:		日期: 2010.08.12	规格: USB3.0
单位: mm	比例: 1:1	图幅: A4	审核: 冯应明		日期:	料号: USB-B01
页次:	版本: A/0	核准:	日期:		规格:	
光洁度: √						