



RECOMMENDED PCB LAYOUT
(TOL: ±0.05)

规格说明: Specifications:
电气特性: Electrical:

1. 额定电流: Current Rating
1.0A/contact terminal
2. 额定电压: Voltage Rating
30V DC
3. 接触阻抗: Contact Resistance
50 milliohms MAX
4. 耐电压: Dielectric Withstanding Voltage:
300 V AC AT Sea Level
5. 绝缘阻抗: Insulation Resistance:
100MEGA ohms MIN

物理性能: Mechanical:

1. 插拔力: Connector Mate and Umate Force
Mate force: 3.0kgf (MAX)
Umate force: 0.7kgf (MIN)
2. 端子保持力: Terminal Retention
0.5kgf (MIN)

原材料: Material:

1. 塑胶: Housing:
Hing Temperature Thermoplastics,
Ul 94V-0 LCP Black
2. 端子: Contact: Copper Alloy C5191
3. 外壳: Shell: Copper Alloy C2680

电镀: Finish:

1. 端子: Contact: Plated Gold in Mating Area;
Tin On Solder Tails
2. 外壳: Shell:
Nickel Plating

品名 (ITEM NO)		MICRO USB 5P/F B型有柱 (四脚插板加高1.35)		图号 (DWG. NO)				单位 (UNIT): MM	
料号 (PART NO)				版本 (REV)		A/0		比例 (SCALE) 1:1	
型号 (MODEL NO)				日期 (DATE)		2012.07.08		未注公差 TOLERANCE UNSPECIFIED	
				设计 (DESIGN)		黎乃杰		±0.30	
				审核 (CHECKED)				±0.20	
				核准 (APPROVED)				±0.10	
								±5°	
								±2°	