



备注:

1.材质:

- 1.1胶芯: LCP+30%G.F UL94V-0
- 1.2端子: 磷铜, T=0.12mm; 镀半金锡1U"
- 1.3外壳: 不锈钢, T=0.30mm; 或亮锡50μ"
- 1.4接地片: 不锈钢, T=0.10mm;
- 1.5卡片: 不锈钢, T=0.15mm;

2.主要特性:

- 2.1额定电流: 3A
- 2.2接触阻抗: 30mΩ MAX
- 2.3绝缘阻抗: 100MΩ MIN 250V DC
- 2.4耐压测试: 250V AC
- 2.5沾锡性: 温度250±5℃, 时间5±0.5s
- 2.6整体插入力: 3.57kgf MAX
- 耐久前整体拔出力: 0.8kgf MIN
- 耐久后整体拔出力: 0.60kgf MIN(匹配021专用母座)
- 2.7使用寿命: 10000次
- 2.8工作温度: -30℃~+80℃

TOLERANCES		<h1>XYFWCN</h1>		
.X	±0.30			
.XX	±0.20	TITLE: USB C TYPE 3.1母座双排贴片(有柱)		
.XXX	±0.10	PART NO.: USB-A12		
ANGLES ±3.00°		DRAWING NO.: 036-011		
APPD.:		REV.:	SIZE:	UNIT:
CHECK:		A/O	A4	M M
DRAWN: LTY		SCALE:	1:1	SHEET: 1/1